



ELEKTRO-ISOLA A/S

G-ETRONAX EP 10 tubes/sheets

No.: 20, 21, 60, 61

G-ETRONAX EP 22 tubes / G-ETRONAX EP 203 sheets

G-ETRONAX EP 11 tubes/sheets

G-ETRONAX EP 11 green

G-ETRONAX EP 215 S

G-ETRONAX EP S

SAFETY DATA SHEET

Safety Data Sheet according to (EC) No. 1907/2006 (REACH).

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier:

See above

1.2. Relevant identified uses of the substance or mixture and uses advised against:

Industrial laminate.

1.3. Details of the supplier of the safety data sheet:

Elektro-Isola A/S Tel: + 45 76 42 82 00

Grønlandsvej 197 Fax + 45 75 82 73 36

DK-7100 Vejle www.elektro-isola.com

Denmark E-mail: ei@elektro-isola.dk

Responsible person for the safety data sheet (e-mail): ei@elektro-isola.dk

1.4. Emergency telephone number:

+45 82 12 12 12 (24-hour service)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture:

According to Regulation 1272/2008 (CLP) the industrial laminate is not a chemical product and therefore does not require a classification.

This Safety Data Sheet is intended as a service to customers/users of the laminate.

2.2. Label elements:

None.

2.3. Other hazards: The material does not constitute any health risk, but careless handling may cause skin abrasion.

Dust from machining (e.g. milling, drilling, sawing, planning, grinding/polishing) may constitute minor health risks - see SECTION 8.

PBT/vPvB: No ingredients are PBT/vPvB, according to the criteria in REACH Annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures:

Product description: Cured epoxy resin on glass-fabric substrate.

Components contributing to the hazard:

May contain minute amounts of: Bisphenol A (CAS No.: 80-05-7, EINECS: 201-245-8)

SECTION 4: First aid measures (if user is exposed to dust from machining)

4.1. Description of first aid measures:

Symptomatic treatment.

Inhalation: Move user to fresh air. Keep under surveillance. If needed: Seek medical advice.

Skin contact: Fibrous glass can irritate the skin, making it more sensitive to chemicals. Remove clothes contaminated with dust fibres. First rinse the skin with plenty of water and then wash the skin with soap and water.

SECTION 4: First aid measures (if user is exposed to dust from machining)

(continued)

Eye contact: Flush eyes well with copious quantities of water or normal saline. If irritation persists: Seek medical advice.

Ingestion: Not relevant.

4.2. Most important symptoms and effects, both acute and delayed:

Inhalation of large amounts of machining dust may cause acute respiratory problems such as asthma. Dust may irritate the eyes. Prolonged or frequent exposure may cause chronic respiratory problems.

4.3. Indication of any immediate medical attention and special treatment needed:

Show this Safety Data Sheet to a physician or emergency ward.

SECTION 5: Firefighting measures

5.1. Extinguishing media:

Water preferred, foam may be used.

5.2. Special hazards arising from the substance or mixture:

Do not breathe smoke gasses: carbon monoxide, phenols, formaldehyde.

5.3. Advice for firefighters:

When entering burning area: Wear self contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures:

Not relevant.

6.2. Environmental precautions:

Not relevant.

6.3. Methods and material for containment and cleaning up:

Dampen dust with water. Then transfer material to a suitable container.

6.4. Reference to other sections:

Not relevant.

SECTION 7: Handling and storage

7.1. Precautions for safe handling:

See SECTION 8.

7.2. Conditions for safe storage, including any incompatibilities:

Clean and dry.

7.3. Specific end use(s):

See SECTION 1

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters:

Occupational exposure limits: Comply with national and local regulations for dust exposure.

DNEL/PNEC: No CSR.

8.2. Exposure controls:

Maintain sufficient local exhaust and ventilation when machining. Ventilated air should not be recycled.

Personal protective equipment:

Inhalation: If the local exhaust ventilation is insufficient when machining: Use an approved mask with a particle filter: Type P2. The filter has a limited lifetime and must be changed. Read the instruction.

Skin: Gloves: Normally not required but may prevent skin abrasion during machining.
Exposed skin may require protection owing to irritation caused by glass fibre particles.

Eyes: When machining, protect eyes from dust and flying chips with safety goggles.

Environmental exposure controls: None particular.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties:

Appearance: Solid. Green sheets and tubes

Odour: Odourless

Odour threshold: No available data

pH: Not applicable

Melting point / freezing point (°C): Not applicable

SECTION 9: Physical and chemical properties (continued)

Initial boiling point and boiling range (°C):	Not applicable
Decomposition temperature (°C):	See SECTION 10
Flash point (°C):	> 200
Evaporation rate:	Not applicable
Flammability (solid, gas):	Not applicable
Upper/lower flammability or explosive limits (vol-%):	Not applicable
Vapour pressure (bar, 20°C):	Not applicable
Vapour density (air=1):	Not applicable
Relative density (g/ml, 20°C):	1.8
Solubility:	Not applicable
Partition coefficient: n-octanol/water, Log K _{ow} :	Not soluble in n-octanol or water
Auto-ignition temperature (°C):	> 200
Viscosity:	Not applicable
Explosive properties:	Not applicable
Oxidising properties:	Not applicable
9.2. Other information:	
None relevant	

SECTION 10: Stability and reactivity

10.1. Reactivity:

Chemically inert. Does not attack other materials.

10.2. Chemical stability:

See SECTION 10.1.

10.3. Possibility of hazardous reactions:

See SECTION 10.1.

10.4. Conditions to avoid:

Sensitivity to mechanical impact: Not sensitive.

Sensitivity to static discharge: Not sensitive. May build up static electricity during handling, depending upon the atmospheric conditions.

Dust explosion hazard: None.

Thermal decomposition: Will decompose as a function of temperature and time at temperatures above 160°C.

10.5. Incompatible materials:

None.

10.6. Hazardous decomposition products:

See SECTION 5.

SECTION 11: Toxicological information (when machining)

11.1. Information on toxicological effects:

Not relevant for industrial laminate.

Information on likely routes of exposure: May be absorbed by inhalation (lungs).

Synergistic products: Tobacco smoke may enhance the effects of inhalation of machining dust.

Symptoms:

Inhalation: Inhalation of large amounts of machining dust may cause acute respiratory problems such as asthma.

Skin: Glass fibre dust is a contact irritant.

Eyes: Glass fibre dust is a contact irritant.

Ingestion: Not relevant.

Chronic effects: Prolonged or frequent exposure may cause chronic respiratory problems if not prevented by personal protective measures and/or engineering controls such as local exhaust. When machining the laminate, small amounts of bisphenol A can be released. Bisphenol A is classified with possible risk of impaired fertility.

Sensitization to product: Phenol A released by machining may cause sensitization (allergy).

Carcinogenicity of product: Glass filaments are not classifiable as to their carcinogenicity to humans by IARC (Group 3).

The size of the continuous filament glass fibres used in this laminate is outside the respirable range, 3 microns or less, thus minimising the potential for any chronic pulmonary effects. The diameter of the used continuous filament glass fibres is 5-14 µm (typically 12 µm). Machining of these fibres does not reduce their diameter, and thus does not increase their potential respirability.

SECTION 12: Ecological information

12.1. Toxicity:

Not applicable for industrial laminate

12.2. Persistence and degradability:

Not relevant.

12.3. Bioaccumulative potential:

Not relevant.

12.4. Mobility in soil:

Not relevant.

12.5. Results of PBT and vPvB assessment:

Not relevant.

12.6. Other adverse effects:

Not relevant.

SECTION 13: Disposal considerations

13.1. Waste treatment methods:

Comply with national and local regulations for inert waste. Recommended means of disposal are incineration or landfill.

EWG-Code: 17 02 03 (Laminate)

SECTION 14: Transport information

Not dangerous goods according to ADR/RID.

14.1. UN-no.: None.

14.2. UN proper shipping name: None.

14.3. Transport hazard class(es): None.

14.4. Packing group: None.

14.5. Environmental hazards: None.

14.6. Special precautions for user: None.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not relevant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture:

The materials fulfil the directives:

2000/53/EC End-of life vehicles.

850/2004/EC On persistent organic pollutants (including PFOS (perfluorooctane sulfonates) and pentabromodiphenyl ether)

1907/2006/EC, annex XVII Concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), (including octabromodiphenyl ether)

2011/65/EC On the restriction of the use of certain hazardous substances in electrical and electronic equipment (ROHS), including decaBDE.

Restriction on application:

Not intended for contact with foodstuffs or animal feed.

Not intended for prolonged skin contact.

Not intended for use in toys for children under 3 years of age.

Not intended for prolonged use at temperatures above 160°C.

15.2. Chemical Safety Assessment:

No CSR

SECTION 16: Other information

Abbreviations:

CMR = Carcinogenicity, mutagenicity og reproductive toxicity.

CSR = Chemical Safety Report

DNEL = Derived No-Effect Level

EC₅₀ = Effect Concentration 50 %

ECB = European Chemicals Bureau.

ECHA = European Chemicals Agency

FW = Fresh Water

LC₅₀ = Lethal Concentration 50 %

LD₅₀ = Lethal Dose 50 %

PBT = Persistent, Bioaccumulative, Toxic

SECTION 16: Other information (continued)

PNEC = Predicted No-Effect Concentration

vPvB = very Persistent, very Bioaccumulative

Special references used:

Troitzsch, J.: International Plastics Flammability Handbook, Hanser Verlag 1990.

IARC = International Agency for Research on Cancer

Training advice:

No special training is required. However, the user should be well instructed in the execution of the task, be familiar with this Safety Data Sheet and have normal training in the use of personal protective equipment.

Other information:

None.

Changes since the previous edition:

1.1

Note:

Information contained herein, while accurate to the best of our knowledge, is intended as a health and safety guide and should not be construed as a warranty for any specific properties. However, as conditions of handling and use of this material are beyond our control, we can accept no liability for damages incurred by the use of this material.

It is the responsibility of the user to comply with all applicable local and national laws and regulations, and nothing contained herein is to be construed as a recommendation for use in violation of any patents or of applicable laws or regulations.

Prepared by: Alttox a/s – Tonsbakken 16-18 – DK-2740 Skovlunde - Phone +45 - 38 34 77 98 - Fax: +45 - 38 34 77 99 / PW - Quality control: PH